

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
1 April 2004 (01.04.2004)

PCT

(10) International Publication Number  
WO 2004/026755 A1

(51) International Patent Classification?: B66F 19/00,  
E04F 21/18

(21) International Application Number:  
PCT/NL2003/000650

(22) International Filing Date:  
19 September 2003 (19.09.2003)

(25) Filing Language: Dutch

(26) Publication Language: English

(30) Priority Data:  
1021503 20 September 2002 (20.09.2002) NL

(71) Applicant and

(72) Inventor: OPHUIS, Gerrit [NL/NL]; Haverweg 40,  
NL-7552 DM Hengelo (NL).

(74) Agents: T JONG, Bastiaan, Jacob et al.; Arnold &  
Siedsma, Sweelinckplein 1, NL-2517 GK The Hague  
(NL).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,  
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,  
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,  
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,  
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: LIFT FOR A KITCHEN



(57) Abstract: The invention relates to a device for lifting and positioning objects such as a kitchen worktop or kitchen cabinet, which device comprises: a frame (2), a support surface (8) arranged on the frame (2) for displacement in vertical direction; lifting means (5, 7) for displacing the support surface (8) in vertical direction. Using such a device a kitchen worktop or cabinet can easily be lifted and positioned at the correct height.

WO 2004/026755 A1

WO 2004/026755 A1



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

WO 2004/026755

PCT/NL2003/000650

1

**LIFT FOR A KITCHEN**

The invention relates to a device for lifting and positioning objects such as a kitchen worktop or kitchen cabinet.

The fitting of a kitchen is hard work. Worktops, particularly those of natural stone, can weigh many tens of kilos. Handling and positioning such a worktop is particularly difficult because of its weight. Upper cabinets, which can easily weigh more than 10 kilos, are also difficult to position and arrange because of the height.

It is an object of the invention to provide a device wherein the above stated drawbacks are alleviated, or even avoided.

This object is achieved with a device according to the invention, which device comprises:

- a frame,
- a support surface arranged on the frame for displacement in vertical direction;
- lifting means for displacing the support surface in vertical direction.

A worktop can for instance be placed on the support surface, whereafter it can be displaced in vertical direction with the lifting means and can be positioned such that the worktop can be shifted onto the cabinets.

In a preferred embodiment the support surface is pivotable between a vertical and horizontal position. A worktop can for instance thus be transported to the kitchen in vertical position and then pivoted into the horizontal position in order to thus be positioned in vertical direction

to allow placing on the cabinets.

Bearings are herein preferably arranged in the support surface, whereby the worktop or other object can slide easily over the support surface.

5 In another preferred embodiment of the device according to the invention, the support surface comprises a standing supporting edge on one side. This supporting edge can serve as boundary of the support surface, although if the support surface is pivotable this support surface then also  
10 serves to support the object, such as a worktop.

In yet another embodiment of the device according to the invention, the lifting means comprise at least one hydraulic cylinder. Such a hydraulic cylinder can be easily operated by hand or by foot to thus lift or lower the support  
15 surface.

The frame is preferably further provided with castors. The device can thus be readily displaced in any desired direction.

Yet another embodiment according to the invention  
20 comprises a lever arranged on the frame for pivoting with one end and with one part resting on the support surface. It is thus possible to attach an object to the free end of the lever and, by vertical displacement of the support surface, to displace the object over a greater distance in vertical  
25 direction. This is particularly advantageous in positioning and placing of upper cabinets of a kitchen.

A supporting table is preferably arranged on the other, free end of the lever. The object can then be placed hereon. The supporting table is preferably arranged pivotally  
30 and connected to the frame via a parallelogram construction. This ensures that the supporting table always retains a fixed orientation, for instance a horizontal orientation, irrespective of the vertical displacement.

In a preferred embodiment the orientation of the supporting table is here adjustable.

Yet another embodiment of the device according to the invention comprises at least one stabilizer bar arranged  
5 on the frame. The stability of the device is improved with this stabilizer bar. Particularly when positioning long and heavy objects, such as a kitchen worktop, or if a lever is used, it is important from a safety viewpoint that the stability of the device is increased.

10 These and other features of the invention are further elucidated with reference to the annexed drawings.

Figure 1 shows a perspective view of a first embodiment of the device according to the invention.

Figure 2 shows a perspective view of the device  
15 according to figure 1 provided with a worktop.

Figure 3 shows the device according to figure 1 from a second viewpoint.

Figure 4 shows a perspective view of the device according to figure 1, provided with a stabilizer bar and  
20 lever.

Figure 1 shows an embodiment of device 1. This device 1 has a frame 2 on which are arranged four swivel castors 3. Arranged on frame 2 is a vertical column 4 in which a hydraulic cylinder 5 (see figure 4) is arranged. This  
25 hydraulic cylinder 5 can be operated by means of a pedal 6. A support surface 8 is arranged on hydraulic cylinder 5 by means of pivot arms 7. Support surface 8 can thus be displaced in vertical direction by operating the pedal 6.

Rollers are arranged in the edge of support surface  
30 8 so that an object placed on support surface 8 can be readily shifted over support surface 8.

Figure 2 shows the device 1, wherein a worktop 10 is placed on the support surface. The device can thus also be

used as workbench, and tools G can be placed on worktop 10.

Figure 3 shows device 1 once again, but in a different position. In this figure the support surface 8 is pivoted to a vertical position via pivot arms 7. On support surface 8 are provided supporting pins 11, which form a supporting edge on which a kitchen worktop can for instance be placed. Kitchen worktop A can thus be transported by means of device 1. The kitchen worktop A can further be displaced in vertical direction by operating pedal 6.

In figure 4 the support surface 8 of device 1 has been removed and an arm is placed on the connecting part for the support surface, which arm is coupled to a lever 12 which is arranged pivotally with one end on column 4. A supporting table 13 is arranged on the free end of lever 12. By now displacing the connecting part in vertical direction via pedal 6, the carrying surface 13 is displaced in vertical direction via the lever action of lever 12. It is thus possible to also lift and position upper cabinets.

Stabilizer bars 14 are further arranged to stabilize the device 1. These stabilizer bars 14 are also equipped with a swivel castor 15.

Further provided in lever 12 is a parallelogram construction which can be adjusted by means of wheel 16. Supporting table 13 and lever 12 form part of this parallelogram construction, whereby it is possible to set the position of supporting table 13 by means of wheel 16.

## CLAIMS

1. Device for lifting and positioning objects such as a kitchen worktop or kitchen cabinet, which device comprises:

- a frame,
- 5       - a support surface arranged on the frame for displacement in vertical direction;
- lifting means for displacing the support surface in vertical direction.

2. Device as claimed in claim 1, wherein the  
10 support surface is pivotable between a vertical and a horizontal position.

3. Device as claimed in claim 1 or 2, wherein bearings are arranged in the support surface.

4. Device as claimed in any of the foregoing  
15 claims, wherein the support surface comprises a standing supporting edge on one side.

5. Device as claimed in any of the foregoing claims, wherein the lifting means comprise at least one hydraulic cylinder.

20       6. Device as claimed in any of the foregoing claims, wherein the frame is provided with swivel castors.

7. Device as claimed in any of the foregoing claims, further comprising a lever arranged on the frame for pivoting with one end and with a middle part resting on the  
25 support surface.

8. Device as claimed in claim 7, wherein a supporting table is arranged on the other end of the lever.


9. Device as claimed in claim 8, wherein the

supporting table is arranged pivotally and connected to the frame via a parallelogram construction.


10. Device as claimed in claim 8 or 9, wherein the orientation of the supporting table is adjustable.


5           11. Device as claimed in any of the foregoing claims, further comprising at least one stabilizer bar arranged on the frame.






2/4

FIG. 2

FIG. 3

4/4



**FIG. 4**

## INTERNATIONAL SEARCH REPORT

Application No  
PCT/NL 03/00650

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 B66F19/00 E04F21/18

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 B66F E04F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EP0-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 89 09 521 U (DEBELT) 2 November 1989 (1989-11-02) page 9, paragraph 2 -page 11, paragraph 4 ----	1,2,4-6
X	US 3 111 232 A (BENSON) 19 November 1963 (1963-11-19) the whole document ----	1,2,4-10
X	US 6 010 299 A (JESSWEIN) 4 January 2000 (2000-01-04) column 3, line 1-67 ----	1,2,4, 7-10
X	DE 197 52 708 A (STADLER) 3 December 1998 (1998-12-03) column 3, line 50 -column 4, line 2 ----- -/--	1-4,6

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents :

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*&\* document member of the same patent family

Date of the actual completion of the international search

15 January 2004

Date of mailing of the international search report

26/01/2004

Name and mailing address of the ISA

European Patent Office, P.B. 6818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Van den Berghe, E

## INTERNATIONAL SEARCH REPORT

Application No

PCT/NL 03/00650

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 3 871 477 A (KUEST) 18 March 1975 (1975-03-18) column 1, line 37-62	1,5,6,11
X	US 6 273 662 B1 (FLECKENSTEIN) 14 August 2001 (2001-08-14) the whole document	1,5,6
X	US 4 715 760 A (BROWNING) 29 December 1987 (1987-12-29) column 2, line 42-65	1

# INTERNATIONAL SEARCH REPORT

Application No  
PCT/NL 03/00650

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 8909521	U	02-11-1989	DE 8909521 U1	02-11-1989
US 3111232	A	19-11-1963	NONE	
US 6010299	A	04-01-2000	NONE	
DE 19752708	A	03-12-1998	DE 19752708 A1	03-12-1998
US 3871477	A	18-03-1975	NONE	
US 6273662	B1	14-08-2001	NONE	
US 4715760	A	29-12-1987	NONE	